# JCT1230C 30A SCR

Rev.A.1.1

## DESCRIPTION:

With high ability to withstand the shock loading of large current, JCT1230C SCR provides high dv/dt rate with strong resistance to electromagnetic interference. It is especially recommended for use on solid state relay, motorcycle, power charger, T-tools etc. Package TO-220C is RoHS compliant.




## MAIN FEATURES

| Symbol | Value | Unit |
|---|---|---|
| $I_{T(RMS)}$ | 30 | A |
| $V_{DRM}$ /$V_{RRM}$ | 1200 | V |
| $I_{GT}$ | ≤40 | mA |

## ABSOLUTE MAXIMUM RATINGS

| Parameter | Symbol | Value | Unit |
|---|---|---|---|
| Storage junction temperature range | $T_{stg}$ | -40-150 | ℃ |
| Operating junction temperature range | $T_j$ | -40-125 | ℃ |
| Repetitive peak off-state voltage ($T_j$=25℃) | $V_{DRM}$ | 1200 | V |
| Repetitive peak reverse voltage ($T_j$=25℃) | $V_{RRM}$ | 1200 | V |
| Average on-state current ($T_C$≤93℃) | $I_{T(AV)}$ | 19 | A |
| RMS on-state current ($T_C$≤93℃) | $I_{T(RMS)}$ | 30 | A |
| Non repetitive surge peak on-state current ($t_p$=10ms , $T_j$=25℃) | $I_{TSM}$ | 370 | A |
| Non repetitive surge peak on-state current ($t_p$=8.3ms , $T_j$=25℃) | | 400 | |
| $I^2t$ value for fusing ($t_p$=10ms , $T_j$=25℃) | $I^2t$ | 685 | $A^2s$ |
| Critical rate of rise of on-state current ($I_G$=2×$I_{GT}$ , f=100Hz , $T_j$=125℃) | dI/dt | 200 | A/μs |
| Peak gate current ($t_p$=20μs , $T_j$=125℃) | $I_{GM}$ | 10 | A |

| | | | |
|---|---|---|---|
| Average gate power dissipation ( $T_j$=125℃) | $P_{G(AV)}$ | 1 | W |
| Peak gate power | $P_{GM}$ | 20 | W |
| Peak pulse voltage ($T_j$=25℃; non-repetitive,off-state;FIG.7) | $V_{pp}$ | 0.5 | kV |

## ELECTRICAL CHARACTERISTICS ($T_j$=25℃ unless otherwise specified)

| Symbol | Test Condition | Value | | | Unit |
|---|---|---|---|---|---|
| | | MIN. | TYP. | MAX. | |
| $I_{GT}$ | $V_D$=12V $R_L$=33Ω | - | - | 40 | mA |
| $V_{GT}$ | | - | - | 1 | V |
| $V_{GD}$ | $V_D$=$V_{DRM}$ $T_j$=125℃ $R_L$=3.3kΩ | 0.25 | - | - | V |
| $I_L$ | $I_G$=1.2$I_{GT}$ | - | - | 120 | mA |
| $I_H$ | $I_T$=1A | - | - | 100 | mA |
| dV/dt | $V_D$=800V Gate Open $T_j$=125℃ | 1500 | - | - | V/μs |
| $t_{on}$ | $I_G$=100mA $I_A$=1A $I_R$=100mA $T_j$=25℃ | - | 5 | - | μs |
| $t_{off}$ | | - | 70 | - | |

## STATIC CHARACTERISTICS

| Symbol | Parameter | | Value(MAX.) | Unit |
|---|---|---|---|---|
| $V_{TM}$ | $I_{TM}$=60A $t_p$=380μs | $T_j$=25℃ | 1.55 | V |
| $V_{TO}$ | Threshold voltage | $T_j$=125℃ | 0.76 | V |
| $R_D$ | Dynamic resistance | $T_j$=125℃ | 15 | mΩ |
| $I_{DRM}$ | $V_D$=$V_{DRM}$ $V_R$=$V_{RRM}$ | $T_j$=25℃ | 8 | μA |
| $I_{RRM}$ | | $T_j$=125℃ | 3 | mA |

## THERMAL RESISTANCES

| Symbol | Parameter | Value | Unit |
|---|---|---|---|
| $R_{th(j-c)}$ | junction to case (DC) | 0.85 | ℃/W |
| $R_{th(j-a)}$ | junction to ambient (DC) | 55 | ℃/W |

## ORDERING INFORMATION




## MARKING



**FIG.1:** Maximum power dissipation versus RMS on-state current




**FIG.2:** RMS on-state current versus case temperature




**FIG.3:** Surge peak on-state current versus number of cycles




**FIG.4:** On-state characteristics




**FIG.5:** Non-repetitive surge peak on-state current for a sinusoidal pulse with width $t_p$<10ms, and corresponding value of $I^2t$ (dI/dt<200A/μs)




**FIG.6:** Relative variations of gate trigger current, holding current and latching current versus junction temperature



**FIG.7：** Test circuit for inductive and resistive loads to IEC-61000-4-5 standards.




## LEAD FORMING AND SOLDERING

Refer to the application note “Assembly Instructions for Thyristors in Through-hole Package” released by JieJie Microelectronics

## ORDERING INFORMATION

| Order code | Voltage $V_{DRM}/V_{RRM}$ (V) | IGT(mA) | Package | Base qty. (pcs) | Delivery mode |
|---|---|---|---|---|---|
| JCT1230C | 1200 | 40 | TO-220C | 50 | Tube |

## Document Revision History

| Date | Revision | Changes |
|---|---|---|
| Apr.13, 2023 | A.1.0 | Last update |
| Oct.14, 2025 | A.1.1 | Revise PACKAGE MECHANICAL DATA |

## PACKAGE MECHANICAL DATA




| Ref. | Dimensions | | | | | |
|---|---|---|---|---|---|---|
| | Millimeters | | | Inches | | |
| | Min. | Typ. | Max. | Min. | Typ. | Max. |
| A | 4.40 | | 4.60 | 0.173 | | 0.181 |
| B | 0.70 | | 0.90 | 0.028 | | 0.035 |
| C | 0.45 | | 0.60 | 0.018 | | 0.024 |
| C2 | 1.25 | | 1.35 | 0.049 | | 0.053 |
| C3 | 2.20 | | 2.60 | 0.087 | | 0.102 |
| D | 8.90 | | 9.90 | 0.350 | | 0.390 |
| E | 9.90 | | 10.30 | 0.390 | | 0.406 |
| E1 | 0.80 | | 1.20 | 0.031 | | 0.047 |
| F | 6.30 | | 6.90 | 0.248 | | 0.272 |
| G | 2.40 | | 2.70 | 0.094 | | 0.106 |
| H | 28.00 | | 29.80 | 1.102 | | 1.173 |
| H1 | 2.15 | | 2.55 | 0.085 | | 0.100 |
| I | 4.70 | | 5.10 | 0.185 | | 0.201 |
| K | 9.90 | | 10.30 | 0.390 | | 0.406 |
| L1 | 2.70 | | 3.30 | 0.106 | | 0.130 |
| L2 | 1.14 | | 1.70 | 0.045 | | 0.067 |
| L3 | 2.65 | | 2.95 | 0.104 | | 0.116 |
| M | 4.80 | | 5.20 | 0.189 | | 0.205 |

## DELIVERY MODE




| PACKAGE | OUTLINE | TUBE (PCS) | INNER BOX (PCS) | PER CARTON |
|---|---|---|---|---|
| TO-220C | TUBE | 50 | 1,000 | 5,000 |

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.